

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: AQUALEM C

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

1.3. Details of the supplier of the safety data sheet

Company name: Oil Technics Ltd
Linton Business Park
Gourdon
Aberdeenshire
DD10 0NH
United Kingdom, Scotland

Tel: +44 (0) 1561 361515

Email: info@oiltechnics.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 1561 361515 (24 Hours)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Dam. 1: H318; Aquatic Chronic 2: H411; Skin Sens. 1: H317

Classification under CHIP: Xi: R36; Sens.: R43; N: R51/53

Most important adverse effects: May cause an allergic skin reaction. Causes serious eye damage. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements under CLP:

Hazard statements: H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark

GHS09: Environmental



SAFETY DATA SHEET

AQUALEM C

Page: 2

- Precautionary statements:** P272: Contaminated work clothing should not be allowed out of the workplace.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER or doctor.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM DODECYL BENZENE SULPHONATE - REACH registered number(s): 01-2119565112-48

EINECS	CAS	CHIP Classification	CLP Classification	Percent
246-680-4	25155-30-0	-	Skin Irrit. 2: H315; Eye Dam. 1: H318; Aquatic Chronic 3: H412	5-10%

2-(2-BUTOXYETHOXY)ETHANOL - REACH registered number(s): 01-2119475104-44

EINECS	CAS	CHIP Classification	CLP Classification	Percent
203-961-6	112-34-5	-	Eye Irrit. 2: H319	1-5%

D-LIMONENE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
227-813-5	5989-27-5	-	Flam. Liq. 3: H226; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	1-5%

PRIMARY ALCOHOL ETHOXYLATE - REACH registered number(s): 01-2119980051-45-XXXX

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	68439-45-2	-	Eye Dam. 1: H318; Acute Tox. 4: H302	1-5%

Non-classified ingredients:

WATER

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	7732-18-5	-	-	>80%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

SAFETY DATA SHEET

AQUALEM C

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

[cont...]

SAFETY DATA SHEET

AQUALEM C

Page: 4

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	67.5 mg/m ³	101.2 mg/m ³	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Refer to specific Member State legislation for requirements under Community environmental legislation.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Straw Yellow

Odour: Pleasant

Evaporation rate: Slow

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

[cont...]

SAFETY DATA SHEET

AQUALEM C

Page: 5

Viscosity: Non-viscous

Boiling point/range °C: >35

Relative density: 1.015

Flash point °C: 78

pH: 8

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

ORL	MUS	LD50	6050	mg/kg
ORL	RAT	LD50	4500	mg/kg

D-LIMONENE

ORL	MUS	LD50	5600	mg/kg
ORL	RAT	LD50	4400	mg/kg
SCU	MUS	LD50	3170	mg/kg

[cont...]

SAFETY DATA SHEET

AQUALEM C

Page: 6

PRIMARY ALCOHOL ETHOXYLATE

DERMAL	-	LD50	>2000	mg/kg
ORAL	-	LD50	>300, <2000	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

Daphnia magna	48H EC50	>1000	mg/l
FISH	96H LC50	2700	mg/l

PRIMARY ALCOHOL ETHOXYLATE

ALGAE	LL/EL/IL50	>100	mg/l
Daphnia magna	LL/EL/IL50	1-10	mg/l
FISH	LL/EL/IL50	1-10	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

[cont...]

SAFETY DATA SHEET

AQUALEM C

Page: 7

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Not applicable.

Disposal of packaging: May be reused following decontamination.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

R36: Irritating to eyes.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legend to abbreviations: PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

[cont...]

SAFETY DATA SHEET

AQUALEM C

Page: 8

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = physico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.