

LD750

Siliconized acrylic sealant



PRODUCT INFORMATION

Description

Tremco LD750 is an excellent all-purpose acrylic sealant formulated to provide a fast-setting pliable seal with minimal shrinkage.

Colour

White

Packaging

300 ml Cartridges (24 per Carton)
600 ml Cartridges (20 per Carton)

KEY BENEFITS SUMMARY

- Paintable.
- Mild dew resistance.
- Easy application and tooling
- Siliconized formulation – Improved adhesion to full range of construction substrates

Joint Preparation

Faces should be clean, dry and free from dust, oil, grease, old sealant and any traces of contaminant which may affect adhesion. Any previously applied sealant must be mechanically removed.

- Apply masking tape to prevent contamination of adjacent surfaces.
- Depending on the substrate, please contact Tremco representatives.

Joint Backing

- Closed cell polyethylene backer rod is recommended for the application.

Usage / Purpose

- LD750 is used as a multi-purpose sealant for cracks and joints and is recommended for sealing interior joints between walls and panels, around door frames and baseboards and also joints between bathroom features and walls.

Priming

- Excellent adhesion without primer to concrete, glass, brick, ceramic, wood, steel, galvanized steel. Perform preliminary adhesion tests on critical and unknown surfaces.

Application

- Apply LD750 equally and free of air bubbles directly out of the cartridge onto the surface or into the joint.
- Smooth surface, if necessary, within the film formation time
- If masking tape has been used remove it right after smoothing.

Cleaning

For surfaces and tools that are contaminated by LD750, we recommend appropriate solvents as cleaner. Totally cured material only can be removed mechanically.

Health & Safety Precautions

Safety data sheet must be read and understood before usage.

LD750

Siliconized acrylic sealant

TREMCO

Technical Data

PROPERTY	TEST METHOD	RESULT
Specific Gravity	Internal	1.5
Consistency	ASTM C639	non-sagging
Tack free time	ASTM C679	45-55 min
Cure Rate	Internal	1mm depth/day
Elongation at Break	ASTM D412	250%
Application Temperature		+5°C to +40°C
Storage	Store in shaded dry conditions between +5 °C and + 25 °C.	
Shelf Life	12 months when stored as recommended in original unopened containers.	

Coverage

Joint dimensions width x depth (mm)	Approximate metres per 300 ml cartridge	Approximate metres per 400 ml sausage	Approximate metres per 600 ml sausage
5 x 5	12.0	16	24
8 x 6	6.2	8.3	12.5
10 X 8	3.7	5	7.5
15 x 10	2	2.6	4.0
20 x 12	1.2	1.6	2.5
25 x 15	0.8	1	1.6
30 x 15	0.6	0.8	1.3

Overpainting

LD750 can be overpainted. Allow 2 to 6 hrs. drying before painting, depending upon climatic conditions.

Please Note

Contact with bituminous or tar containing surfaces can lead to discoloring. Application to natural stone substrates is recommended only after appropriate testing.