

EU Type



Model: **SP150**

- Welded steel frame with durable coat finish.
- Durable hydraulic pump ensures a long service life.
- Robust casters with safety wheel guard enhance safety while operation.
- Easy action foot operated foot hydraulic pedal for raising the lift table to a desired height level.
- Safety back guard protects operators from dangers.
- With supporting plat on side of arm to ensure the safety service.
- Convenient finger release smoothly lowers even heavy loads.
- With over load by pass valve to protect operator and pump.



Conforms to EN 1570-1
 Based on Directive 2006/42/EC



Model: **SP800**
SP1000
SP1500



Model: **SP300**
SP500

Specification for EU type

1KG=2.205LB 1INCH=25.40MM

MODEL		SP150	SP300/SP500	SP800	SP1000	SP1500
Capacity	kg	150	300/500	800	1000	1500
Max. lift height	h_{12} (mm)	740	900	1000	1000	1000
Min. height of table	h_{13} (mm)	225	340	420	380	420
Lifting height	h_3 (mm)	515	560	580	620	580
Table size	$l \times b \times s$ (mm)	740x450x35	855x500x50	1000x510x55	1016x510x60	1220x610x60
Total height	h_{14} (mm)	935	970	996	962	962
Overall length	l_1 (mm)	830	925	1150	1170	1379
Foot pedal cycles to max height		≤ 25	$\leq 32 / \leq 45$	≤ 70	≤ 55	≤ 70
Wheel diameter	d (mm)	100	127	150	150	150
Qty. / 20' Container	PCS	192	120	52	52	48
Service weight	kg	44	82/87	115	115	135
Carton size	mm	880x480x265	950x530x390	1180x615x460	1180x615x430	1410x730x450

EU type SP150, SP300, SP500, SP800 in stead of old model SPA150, SPA300, SPA500, SPA800.