

## SpEC Grout Check

### SELF-ADHESIVE FORMWORK SEALING STRIP

#### DESCRIPTION

**SpEC Grout Check** is a self-adhesive polyurethane foam sealing strip that prevents grout loss through joints in the formwork.

#### TYPICAL USES

**SpEC Grout Check** may be used in joints between various types of shuttering panels, such as:

- Timber and plywood
- Steel and aluminium
- GRP and other plastic formwork

#### ADVANTAGES

- Prevents grout leakage from joints in shuttering panels
- Provides a neat finish to the concrete surface
- Self-adhesive - easily applied to clean surfaces in all types of formwork
- Available in different sizes
- Economical

#### TECHNICAL DATA

<b>Form</b>	Compressible polyurethane foam
<b>Adhesion</b>	Self-adhesive surface with peel off paper on one side
<b>Colour</b>	Off - white

#### APPLICATION

Sides of shuttering panels where **SpEC Grout Check** is to be fixed must be clean, smooth and free from grit, dust, grease, oil, cement dropping, etc. Chip out any protrusions and fill large holes, broken endgates, etc.

Peel off a short length of the release paper and stick the adhesive side onto the edge of the first panel. Continue down the side of the panel and cut as required. Press to ensure good contact. Place the adjacent panel in position and press firmly against the **SpEC Grout Check** on the first, making sure that the foam is well compressed.

Check panel joints after removing the formwork to

make sure that **SpEC Grout Check** is firmly in place and replace if necessary. For best results replace old and damaged foam at regular intervals.



## PACKAGING

**SpEC Grout Check** is supplied in individual boxes, in pack of 100 and 120 metres, Available sizes:

Roll Size (thickness x width)	Roll Length	No. of Rolls per Pack
10 x 10 mm	10 m	10
10 x 15 mm	10 m	12
10 x 20 mm	10 m	10

Use the size most suitable for the type and condition of the formwork.

## STORAGE

Store off the ground in dry conditions.

## HEALTH & SAFETY

There are no health hazards associated with normal use of **SpEC Grout Check**.

Dispose of all waste in accordance with the local environmental regulations.

### Other SpEC Formwork Products:

- **SpECbuild MRA** - Chemical Release Agent for All Types of Formwork
- **SpEC Clean Strike EF** - Water Based, Environmentally Friendly from Release Agent
- **SpEC Surface Retarder** - Surface Retarder for Exposed Aggregate Finish.

Issue 4: 10/2013

QA-054

Whilst the information and/or specifications given are, to the best of our knowledge, true and accurate, no warranty is given or implied in any connection with any recommendations or suggestions made by us, our representatives, agents or distributors as the conditions of use and labour involved are beyond our control.

### SPECIALITY ENGINEERING CHEMICALS

PO Box 61347, Dubai, United Arab Emirates. Telephone: +971 4 883 6662, Fax: +971 4 883 7696

E-mail: [info@spec.ae](mailto:info@spec.ae)

[www.spec.ws](http://www.spec.ws)

Distributed by: **EMIRATES SPECIALITIES CO., L.L.C.**

P.O. Box 3880, Dubai, United Arab Emirates.

Al-Quoz Distribution Centre.

Tel: +971 4 3470767, Fax: +971 4 3470765

E-mail: [dubai@esco.ae](mailto:dubai@esco.ae)

P.O. Box 46564, Abu Dhabi, United Arab Emirates.

Tel: +971 2 6784800, Fax: +971 2 6778366

Email: [abudhabi@esco.ae](mailto:abudhabi@esco.ae)

P.O. Box 6156, Sharjah, United Arab Emirates

Tel: +971 6 5420220, Fax: +971 6 5421211

Email: [sharjah@esco.ae](mailto:sharjah@esco.ae)

**“Printed on Recycled Paper”**